



Flammable Liquid Storage Cabinets

Features:

- Built in double wall steel with 38mm of insulating air space.
- 3 units (RFC-600) or 2 units (RFC-450) or 1 unit (RFC-300 & 120) of heavy duty adjustable shelf.
- 50 mm liquid-tight containment sump.
- Lateral high and low vent 50mm diameter with flame arresters.
- Continuous piano hinge.
- Manual full opening doors.
- 2 point lock with key system and handle.

Option:

- Additional shelf.
- Ventilation or filtration boxes.



Model: RFC-300



Model RFC-450



Adjustable shelves



Model RFC-600



Vent with built-in flame arresters



Continuous piano hinge



Liquid-tight containment sump



2-point lock with key system

SPECIFICATIONS

Model	RFC-120	RFC-300	RFC-450	RFC-600
Body construction	1.2mm thick electro-galvanize steel sheet in high quality epoxy coating.			
Capacity	(45 liters) 12 gallons	(113 liters) 30 gallons	(170 liters) 45 gallons	(220 liters) 60 gallons
Adjustable Shelves supplied	1 pc	1 pc	2 pcs	3 pcs
Shelve dimensions (mm)	520W x 380D x 35H	1000W x 356D x 30H		
Door type	Twin doors, 2 point latch			
External dimensions (mm)	615W x 500D x 970H	1090W x 460D x1120H	1090W x 460D x1650H	1090W x 460D x1950H
Internal dimensions (mm)	530W x 380D x 855H	1005W x 390D x1025H	1005W x 390D x1560H	1005W x 390D x1860H
Weight	46 kg	105 kg	140 kg	170 kg

Manufactured In Accordance with OSHA & NFPA code 30 specifications.