

QRLab Flammable Liquids Storage Cabinets

Features:

- Constructed of double wall, 18-gauge steel with 38 mm (1½-inch) of insulating air space.
- 3 point lock with key and handle.
- Lateral high and low dual vents with flame arresters.
- Full length piano hinges.
- 2-inch (5 cm) raised, leak-proof door sill to contain spills.
- Each self can support up to 160kg (350 lbs) load.
- 4 adjustable levelling feet.

Option:

- Additional shelf.
- Filtration boxes.



Model: QRFC-450

Safety Practices for Flammable Liquid Storage

- Do not store paper or cardboard or other combustible material in a flammable storage cabinets.
- Store only compatible materials inside a flammable storage cabinets.
- No more than 60 gallons (227 Litres) of Class I flammable liquids (Flash point below 100°F) or Class II combustible liquids (Flash point between 100°F to 140°F) may be stored in a flammable liquid storage cabinets.
- No more than 120 gallons (454 Litres) of Class III combustible liquids (Flash point between 140°F to 200°F) may be stored in a flammable liquid storage cabinet.
- Not recommended for storage of phenol, nitric acid or sulfuric acid.



Model: QRFC-120

Advantages of Flammable Liquid Storage Cabinets

- Reduces and eliminates flammable which caused by open storage of chemical containers.
- Offer a safe storage for short period of time. It reduces the frequency of trips to the drum storage or dispensing facility.
- Flammable liquid storage cabinets are not recommended for the storage of highly toxic materials, acids, bases, compressed gases or pyrolytic chemicals.

SPECIFICATIONS

Model	QRFC-120	QRFC-300	QRFC-450	QRFC-600	QRFC-900
Capacity	12 gallons (45 litres)	30 gallons (113 L)	45 gallons (170 L)	60 gallons (227 L)	90 gallons (340L)
Cabinets construction	Powder coated paint finish 18-gauge steel sheet.				
Shelves dimensions (mm)	520Wx380Dx35H	825Wx530Dx35H	970Wx365Dx35H	736Wx735Dx35H	970Wx735Dx35H
No of shelves	1 unit	1 unit	2 units	2 units	2 units
Exterior dimensions (mm)	615W x 500D x 970H	920Wx650Dx910H	1075Wx500Dx1650H	863Wx863Dx1650H	1075Wx863Dx1650H
Interior dimensions (mm)	530Wx380Dx855H	840Wx530Dx810H	995Wx385Dx1580H	767Wx758Dx1585H	995Wx758Dx1585H
Weight	46 kg	78 kg	171 kg	194 kg	230 kg

Manufactured In Accordance with OSHA Regulations & NFPA code 30 specifications.