



2°C ~ 8°C Pharmacy Refrigerator Bench-Top & Upright Type

REMI pharmacy refrigerators are designed to store pharmaceutical products, medicine, and other related products. This product is applicable to clinics, hospitals, pharmacy stores, epidemic prevention services, and food services.

Precise Temperature Control

- Microprocessor control with LED temperature display give a temperature reading up to 0.1°C.
- Forced-air circulation system ensuring temperature range of 2°C ~ 8°C.
- Controller is designed with compressor delay start up Temperature off set calibration, Auto defrost.

Alarm systems

- Alarm Buzzer & Temperature Display backup system can last for 12 hours during power failure if battery is fully charged.
- The alarm system will alert through buzzer sound or alarm message if the below conditions occur: Out of limits for High and Low alarm setting, Power failure(Optional), Door open more than 3 minutes.

Cooling System

- High efficient compressor and CFC-FREE refrigerant is used to have fast cooling effects.
- Forced-Air circulation system ensuring superior temperature uniformity.

Ergonomic Design

- Automatic cycle defrost ensure no rise in cabinet temperature.
- The double glass door give a comprehensive view for the storage samples.
- Safety door lock is designed to prevent unauthorized access.



Model: BC-59G



Model: BC-140G

SPECIFICATIONS

Model	BC-59G	BC-140G
Cabinet Construction (External)	Epoxy Coated Mild Steel	
Cabinet Construction (Internal)	Painted aluminium	PS Plastic
Foaming Insulation	R141b	
Door	Single swing-out heated glass door	
Temperature working range	2°C to 8°C (Pre-set at 4°C)	
Temp. Setting & Display	LED Digital Display to 0.1°C)	
Alarm system	Audible and Visual alarms	
Alarm conditions	High & Low alarm, Door open, Power Failure alarm (Optional)	
Compressor	1 unit Reciprocating Hermetic Compressor	
Refrigerant	R134a/R600a, CFC FREE	
Defrosting	Automatic cycle defrost	
Power Supply	220-240 Vac, 50 Hz, Single phase	
Power Input/ main fuse minimum	125 Watts/ 0.95A	125 Watts/ 0.86A
Power consumption	1.0kWh/ 24h	1.65kWh/ 24h
Max noise level	50dbA	50dbA
Capacity Liters / cu.ft	59 liters/ 2.08 cu.ft	145 liters/ 5.12 cu.ft
Chamber dimensions (mm) WxDxH	361 x 370 x 590	495 x 440 x 728
Overall dimensions (mm) WxDxH	445 x 485 x 725	595 x 595 x 820
Shelves	3 coated wire shelves	3 coated wire shelves
Door Lock	1 unit of door lock	
Weight	33 kg	45 kg
Standard Comply	CE Marks, ISO13485	